

SPRAY NOZZLE**FIELD OF THE INVENTION**

The invention relates to a spray nozzle for spraying
5 fountain solution or the like on a roll in a printing
machine. The spray nozzle comprises a spray opening on a
front end of the spray nozzle, and a base plateau situated
on a level between the front end and an opposite rear end
of the spray nozzle.

10 PRIOR ART

Spray nozzles for spraying fountain solution on a
roll in a printing machine are known e.g. from US-A-5 595
116.

It is a well-known fact that such spray nozzles tend
15 to get clogged due to impurities in the air in the vicinity
of the printing machine. The impurities tend to build up
close to the nozzle opening. In order to minimize the
problem with nozzle clogging, several different air caps
have been used to protect the nozzle from negative
20 influences of impurities in the air. Such an air cap has an
opening for the spray, through which low-pressure air is
directed, in the same direction as the spray, which gives
the spray nozzle a clean environment to work in.

One problem with air caps is that it is difficult to
25 retrofit existing spray systems with air-capped nozzles.

During operation of prior art nozzles, it has been
found that the impurities start to build up on sloping
sides, in the vicinity of the spray opening. As operation
continues, the size of the clogged area increases, and gets
30 closer and closer towards the spray opening. Finally, the
spray from the spray opening is adversely affected.

One theory regarding the impurity build up is that a
recirculation zone is created in the vicinity of the spray
opening. Due to this recirculation, dirt in the ambient air

is transported from the air towards the sloping sides. As the dirt carrying recirculating flow from the ambient air hits the sloping sides, the dirt starts to build up.

One option to reduce the clogging of the nozzle is hence to make design changes of the nozzle in the vicinity of the spray opening, in order to change the recirculating flow. Such design changes are beneficial in that it is very easy to retrofit existing spray systems with redesigned nozzles.

10 SUMMARY OF THE INVENTION

The invention solves or reduces the above mentioned clogging and other problems by means of a spray nozzle according to claim 1. Preferred embodiments of the invention are described in the dependent claims.

15 BRIEF DESCRIPTION OF THE DRAWINGS

In the following, the invention will be described by means of an embodiment, with reference to the appended drawings, wherein

Fig. 1 is a top plan view of a flat-spray nozzle according to the present invention;

Fig. 2 is a section view of the flat spray nozzle, taken along the line B-B of Fig. 1; and

Fig. 3 is a section view of the flat spray nozzle, taken along the line A-A of Fig. 1.

25 DESCRIPTION OF AN EMBODIMENT

Figs. 1, 2, and 3 show three different views of a spray nozzle 100 comprising a spray opening 110 that opens on an elevated protrusion 120. In the following, the end of the nozzle comprising the spray opening will be referred to as "front end", while the opposite end thereof will be referred to as "rear end". The elevated protrusion 120 protrudes from a base plateau 130, which connects to sloping sides 140. All the above-mentioned components are

situated within enclosing walls 150. The enclosing walls 150 connect to surfaces 160, which in turn connect to a circumferential guiding wall 170. Further, a holding surface 180 is provided in the vicinity of the

5 circumferential guiding wall 170, close to the rear end of the nozzle 100. The rear end also comprises a sealing surface 190. The sealing surface 190 and the holding surface 180 are connected by a second circumferential guiding surface 200. Finally, the nozzle 100 comprises a

10 channel 210 that connects the rear end of the nozzle with the spray opening 110.

During operation, a liquid to be sprayed is supplied to the rear end of the channel 210, whereupon the liquid is transported to the spray opening 110 and sprayed through

15 spray opening 110, which gives a flat spray cone as shown by the dashed lines S of Figs. 2 and 3.

In the following, the function of the spray nozzle 100 will be described.

The nozzle 100 is attached to a nozzle holder (not shown) by means of a threaded nut (not shown) with a

20 shoulder engaging the holding surface 180. During the attachment of the nozzle 100 on the nozzle holder, the nozzle 100 is guided to the right position on the holder by means of the circumferential guiding surfaces 170 and 200.

25 The sealing surface 190 provides a seal between the nozzle holder and the nozzle. To improve the sealing, a gasket or O-ring can be provided between the sealing surface 190 and the nozzle holder. In other embodiments, the seal between the nozzle holder and the nozzle can be provided in other

30 ways, e.g. by means of a protrusion from the holder, which protrusion protrudes into the channel 210. The connection between the channel and the protrusion from the holder is preferably sealed by means of an O-ring.

The function of the enclosing walls 150 is two-

35 folded; on one hand, they enclose the spray opening 110,

and serve as a director for the airflow in the vicinity of the spray; on the other hand, they can serve as guides for an air cap.

5 The sloping sides 140 guide the airflow in the vicinity of the spray opening. On prior art devices, the sloping sides 140 reach all the way up to the spray opening 110, which means the elevated platform 120 and the base plateau 130 actually are the same surface. In other
10 sloping sides at all, but let the base plateau go all the way out to the guiding surface 170.

The major difference between the prior art nozzles and the nozzle 100 according to the present invention is that the spray opening 110 opens on a protrusion 120, that
15 protrudes over the base plateau 130. The height of the protrusion is, in one embodiment, about 2 mm, but can vary within large limits without departing from the scope of the invention. In one preferred embodiment, the front area of the protrusion is about 2 by 2 mm, i.e. about the length of
20 the oblong spray opening. In the preferred embodiment, the base plateau is about 5 by 5 mm, i.e. the distance between the inner sides of the enclosing walls 150 is 5 mm. The thickness of the enclosing walls is about 1.5 mm, i.e. the distance between the outer sides of the enclosing walls 150
25 is 8 mm. The sloping sides 140 connect to the guiding surface 170 at a distance of 5 mm from the rear end of the nozzle 100, and has a slope relative to a length axis of the nozzle of about 45 degrees. The diameter of the guiding surface 170 is, in a preferred embodiment, about 12 mm.

30 The total height of the nozzle 100 is about 10 mm, and the diameter of the guiding surface 200 is about 15 mm. Finally, the width of the spray opening is about 0.2 mm, and its length is, as mentioned, 2 mm. The dimension of the channel 210 is not important, as long as it is wide enough

not to restrict the flow of liquid to be sprayed on its way from the nozzle holder to the spray opening 110.

Preferably, the nozzle is manufactured from stainless steel, but also other materials resistant to a misty
5 environment could be used, e.g. tungsten, plastics, titanium, aluminum, nickel, or the like.

The dimensions above are given for the sole purpose of describing a preferred embodiment, and are not limiting the scope of the invention. The scope of the invention is
10 defined in the appended claims.

CLAIMS

1. A spray nozzle (100) for spraying fountain solution or the like on a roll in a printing machine, the spray nozzle (100) comprising a spray opening (110) at a base plateau (130) at a front end of the spray nozzle, **characterized in that** the spray opening (110) opens on a protrusion (120) protruding from the base plateau (130) in the spray direction of the nozzle (100).
2. The spray nozzle (100) according to claim 1, wherein the spray opening (110) is oblong, and hence gives a flat spray.
3. The spray nozzle (100) according to claim 1 or claim 2, wherein sloping sides (140) connect slope rearwardly from the base plateau (130).
4. The spray nozzle (100) according to any of the preceding claims, wherein the protrusion (120) protrudes about 2 mm over the base plateau (130).
5. The spray nozzle (100) according to any of the preceding claims, wherein the protrusion has a front area of about 2 by 2 mm.
6. The spray nozzle (100) according to any of the preceding claims, wherein the sloping sides (140), the spray opening (110), the base plateau (130) and the protrusion (120) are enclosed by enclosing walls (150).
7. The spray nozzle (100) according to any of the preceding claims, wherein the sloping sides (140) slope with an angle of about 45 degrees.

8. The spray nozzle (100) according to any of the preceding claims, wherein the nozzle (100) is manufactured from a uniform piece of material.

5 9. The spray nozzle (100)) according to any of the preceding claims, wherein the nozzle is manufactured from stainless steel.

10

1/1

Fig. 1




Fig. 2





Fig. 3



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000890

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B41F 7/30, B05B 1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B41F, B06B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6293476 B1 (N.T. PETTIT), 25 Sept 2001 (25.09.2001) --	1-9
A	US 4891249 A (F.S. MCINTYRE), 2 January 1990 (02.01.1990) --	1-9
A	US 4708058 A (G.R. SMITH), 24 November 1987 (24.11.1987) --	1-9
P,A	EP 1361045 A1 (KABUSHIKI KAISHA TOKYO KIKAI SEISAKUSHO), 12 November 2003 (12.11.2003) --	1-9

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

14 Sept 2004

Date of mailing of the international search report

22 -09- 2004

Name and mailing address of the ISA/

Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM

Authorized officer

Teija Rasch / MRO

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 2004/000890

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0422400 A2 (ROCKWELL INTERNATIONAL CORPORATION), 17 April 1991 (17.04.1991) --	1-9
A	EP 0621134 A1 (JIMEK INTERNATIONAL AB), 26 October 1994 (26.10.1994) --	1-9
A	GB 666247 A (E.J. MARSHALL ET AL), 6 February 1952 (06.02.1952) -- -----	1-9

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

INFORMATION ON PATENT FAMILY MEMBERS

31/07/2004

International application No.

PCT/SE 2004/000890

US	6293476	B1	25/09/2001	CA	2349387 A	28/12/2001
				EP	1166884 A	02/01/2002
				JP	2002028540 A	29/01/2002

US	4891249	A	02/01/1990	AU	610168 B	16/05/1991
				AU	1608788 A	01/12/1988
				BR	8802576 A	20/12/1988
				CN	1030032 A	04/01/1989
				EP	0293065 A	30/11/1988
				FI	882313 A	27/11/1988
				IL	86272 A	29/03/1992
				JP	1058370 A	06/03/1989
				US	4996091 A	26/02/1991

US	4708058	A	24/11/1987	EP	0257195 A	02/03/1988
				JP	63072549 A	02/04/1988

EP	1361045	A1	12/11/2003	JP	2003326669 A	19/11/2003
				US	2003209613 A	13/11/2003

EP	0422400	A2	17/04/1991	SE	0422400 T3	
				CA	2025331 A,C	11/04/1991
				DE	422400 T	26/09/1991
				DE	69014066 D,T	27/04/1995
				JP	2111662 C	21/11/1996
				JP	3132348 A	05/06/1991
				JP	8029580 B	27/03/1996
				US	5040457 A	20/08/1991

EP	0621134	A1	26/10/1994	DE	69406707 D,T	12/03/1998
				SE	507913 C	27/07/1998
				SE	9301360 A	24/10/1994

GB	666247	A	06/02/1952	NONE		

BEST AVAILABLE COPY